ZONLION SCISSOR LIFTS ROUGH TERRAIN

Comply with CE/ANSI/CSA Standard

HIGHLIGHTS

- ► Reliable auto-leveling function
- ▶ 1500lb/680kg platform capacity
- ▶ 4ft 3in platform extension
- ▶ Bilateral swing-out trays, simple to service and effective to control noise
- ▶ Smart telematic control interface with self-diagnostic monitoring capability


FEATURES

Standard Features

Proportional controls	On-board diagnostic	
All motion alarm	Over tilt protective system	
Fold-down handrails	Horn	
Flashing beacon	Hour meter	
Self-closing entry gate	Extension deck (bidirectional)	
Autobrake system	Scissor maintenance prop	
Emergency descent system	Load sensing system	
Emergency stop button	AC power to platform	

Accessories & Options

- ▶ Platform work lights
- ► Air line to platform



ACCESS WITH ZOOMLION GREEN



MAIN SPECS OF SCISSOR LIFTS

ROUGH TERRAIN

Comply with CE/ANSI/CSA Standard

Model	ZS5390RT		
	Imperial	Metric	
	Size		
Work Height	59ft	18m	
A Platform Height-Elevated	52ft 6in	16m	
B Platform Height-Stowed	6ft 8in	2.03m	
C Platform Dimension (Length)	13ft 1in	3.98m	
D Platform Dimension (Width)	6ft	1.83m	
Platform Extension	4ft 3in	1.3m	
Overall Height (Rails Up)	10ft 4in	3.16m	
E Overall Height (Rails Down)	8ft 1in	2.47m	
F Overall Length	16ft	4.88m	
G Overall Width	7ft 7in	2.3m	
H Wheelbase	9ft 6in	2.9m	
l Ground Clearance	11in	0.275m	
	Performance		
Platform Capacity	1500lb	680kg	
Capacity on Deck Extension	510lb	230kg	
Drive Height	29ft 6in	9m	
Max. Number of Workers	4		
Drive Speed (Stowed)	4mph	6.5km/h	
Drive Speed (Raised)	0.3mph	0.5km/h	
Turning Radius (Inside)	9ft	2.75m	
Turining Radius (Outside)	19ft	5.8m	
Up/Down Time	60/65s		
Gradeability	40%		
Max. Working Slope (Lateral/Vertical)	2°/3°		
Drive	4WD		
Tire	315/55 D20 Foam-filled Tires		
	Power		
Engine	Kubota v2403-M-DI		
Engine Power	36kw/2600rpm		
Hydraulic Tank Capacity	27.7 (us gal)	105L	
Diesel Tank	26.4 (us gal)	100L	
Weight			
Gross	19070lb	8650kg	

